TC Systems, Inc.	Section 4
P.S.C. No. 7 Telephone	Leaf No. 4
Access Services	Revision: 0
Effective Date: December 23, 2011	

SECTION 4 - CALL COMPLETION SERVICE

4.1 Call Completion Service (Cont'd)

- 4.1.3 Provisioning and Description of FGD (Cont'd)
 - B. Calling Party Number (CPN) [Where permitted]. This option provides for the automatic transmission of the calling party's ten digit telephone number to the customer's premises for originating calls. The tendigit telephone number consists of the NPA plus the seven-digit telephone number, which may or may not be the same as the calling station's charge number. The protocol for CPN is contained in Technical Reference TR-TSV-000905. This feature is only available when out of band signaling is specified.

TCG will transmit a "privacy indicator" as part of the CPN information in those jurisdictions where end users may elect that their CPN information may not be passed to the called party, and where the end user has taken the necessary actions to ensure that their CPN is so blocked.

- C. Charge Number (CN) This option provides for the automatic transmission of the ten-digit billing number of the calling station number and originating line information. The protocol for CN is contained in Technical Reference TR-TSV-000905. This feature is only available when out of band signaling is specified.
- D. Carrier Selection Parameter (CSP) This option provides for the automatic transmission of a signaling indicator which signifies to the customer whether the call being processed originated from a presubscribed end user of that customer. The protocol for CSP is contained in Technical Reference TR-TSV-000905. This feature is only available when out of band signaling is specified.
- E. 800 Data Base Access Service and Toll Free Transit Traffic Service.

800 Data Base Access Service is an originating only trunk side service. When an 800+NXX+XXXX call is originated by an end user, TCG will perform customer identification based on screening of the full ten-digits of the 800 number to determine the location to which the call is to be routed.