

PSC NY No. 11--COMMUNICATIONS

Verizon New York Inc.

Section 6
Original Page 23

ACCESS SERVICE

6. SWITCHED ACCESS SERVICE (Cont'd)6.1 General (Cont'd)6.1.2 Rate Categories (Cont'd)(A) Local Transport (Cont'd)(1) Interface Groups (Cont'd)(g) Glossary of Premises Interface Codes

<u>Code</u>	<u>Option</u>	<u>Definition</u>
AH -		analog high capacity interface
-	B	60 kHz to 108 kHz (12 channels)
-	C	312 kHz to 552 kHz (60 channels)
-	D	564 kHz to 3084 kHz (600 channels)
DS -		digital hierarchy interface
-	15	1.544 Mbps (DS1) format per PUB 41451 plus D4
-	15L	1.544 Mbps (DS1) with SF signaling
DX -		duplex signaling interface at customer's point of termination
EA -	E	Type 1 E&M Lead Signaling. Customer at POT or customer's end user at POT originates on E Lead.
EA -	M	Type 1 E&M Lead Signaling. Customer at POT or customer's end user at POT originates on M Lead.
EB -	E	Type II E&M Lead Signaling. Customer at POT or customer's end user at POT originates on E Lead.
EB -	M	Type II E&M Lead Signaling. Customer at POT or customer's end user at POT originates on M Lead.
EC-		Type III E&M signaling at customer POT.
EX -	B	tandem channel unit signaling for loop start or ground start and customer supplies closed end (dial pulsing, etc.) functions.

Issued: August 1, 2001

Effective: September 1, 2001

By Sandra Dilorio Thorn, General Counsel
1095 Avenue of the Americas, New York, N.Y. 10036