Received: 09/04/2012 Status: CANCELLED Effective Date: 09/01/2001

PSC NY No. 11--COMMUNICATIONS

Verizon New York Inc.

Section 6 Original Page 62

ACCESS SERVICE

6. SWITCHED ACCESS SERVICE (Cont'd)

6.3 <u>Local Switching Optional Features</u> (Cont'd)

6.3.1 Common Switching Optional Features (Cont'd)

(K) <u>Dial Pulse Address Signaling</u>

This trunk side option provides for the transmission of number information, e.g., called number, between the end office switching system and the customer's premises (in either direction) by means of direct current pulses. It is available with Feature Group C.

(L) Panel Call Indicator Address Signaling

This option provides a dc pulsing arrangement in which each digit is transmitted as a series of four marginal and polarized impulses. It is available with Feature Group C.

(M) Service Class Routing

This option provides the capability of directing originating traffic from an end office to a trunk group to a customer designated premises based on the line class of service (e.g., coin, multiparty or hotel/motel), service prefix indicator (e.g., 0-, 0+, 01+ or 011+), service access code (e.g., 800 or 900) and/or bearer capability. With the exception of Service Class Routing by bearer capability, Service Class Routing is provided in suitably equipped end office or access or TOPS tandem switches and is available as a nonchargeable option with Feature Group C or D. Service Class Routing by bearer capability is only available in suitably equipped end offices as a nonchargeable option with Feature Group D when ordered with the SS7 Signaling Option.

(N) Alternate Traffic Routing

This option provides the capability of directing originating traffic from an end office (or appropriately equipped access tandem) to a trunk group (the "high usage" group) to a customer designated premises until that group is fully loaded, and then delivering additional originating traffic (the "overflowing" traffic) from the same end office or access tandem to a different trunk group (the "final" group) to a second customer designated premises. The customer shall specify the last trunk CCS desired for the high usage group. It is provided in suitably equipped end office or access tandem switches and is available with Feature Groups C and D.

Issued: August 1, 2001 Effective: September 1, 2001

By Sandra Dilorio Thorn, General Counsel 1095 Avenue of the Americas, New York, N.Y. 10036