
SECTION 6 - SUPPLEMENTAL SERVICES

6.2 PrimeNBX Service Features (Cont'd)

6.2.2 Description of Features (Cont'd)

Display Features:

Display Called Number - Provides the user of an electronic telephone equipped with the optional 32-character alphanumeric Liquid Crystal Diode (LCD) with visual feedback concerning the called number during the origination, termination, programming, and feature activation operations.

Display Calling Number - Provides the electronic display telephone user receiving an incoming call with visual feedback concerning the calling number. (Intra-PrimeNBX Group)

Feature Display - Provides the user of an electronic telephone equipped with the 32-character LCD with visual feedback on user-entered data and incoming call information during the use of other PrimeNBX features.

Time Key - Provides the current time and date on an electronic telephone display.

Distinctive Call Waiting Tones: Permits a called station line user to determine whether an incoming waiting call is external or internal to the customer group by providing different tone cadences for the two situations.

Distinctive Ringing: Provides a unique pattern of ringing to permit the station line user to distinguish between intragroup and DID calls.

Do-not-Disturb: Permits the attendant to cut off a single station line and selected groups of station lines from receiving DID and station-to-station calls.

Enhanced Three-Way Calling: Allows a non-controlling party on a three-way call to add another conferee.

Flexible Console Alerting: Enables an attendant to be alerted to a call requiring attention by an alert tone that is sent through the headset.

Forced Account Codes: Up to six digits can be used by customer to ensure outgoing calls are billed to department or clients.

Group: Allows shared use of a speed calling list. A control station will add, change or delete telephone numbers from the list for the group (maximum of 30 numbers).