
SECTION 3 – DEDICATED ACCESS SERVICES

3.1 Dedicated Access Services (Cont'd)

3.1.3 DS3 Service (44.736 Mbps)

DS3 Service is composed of digital channels provided at 44.736 Mbps for the transmission of one-way and two-way communications. Interconnections to such channels and equipment interfacing to such channels shall meet the following technical characteristics:

Line Rate:	44.736 Mbps +/- 20 ppm
Line Code:	Bipolar with three-zero substitution
Test Load:	75 ohms resistive +/- 5 percent
Power Levels:	For an all-ones transmitted pattern, the power in a 2 KHz band about 22.368 KHz shall be -1.8 to +5.7 dBm and the power in a 2 KHz band about 44.736 MHz shall be at least 20 dB below that in a 2 KHz band about 22.368 KHz. 1

NOTES:

1. The power levels specified by CCITT Recommendation G.703 are identical except that the power is to be measured in 3 KHz bands.

Digital channels at 44.736 Mbps will be provided in one of the following configurations, as specified by the customer:

Clear Channel DS3: A DS3 signal that is transmitted intact and transparently as provided at the customer interface. No performance monitoring is performed since all 44.736 Mbps are considered customer data or voice.

M13 Framed DS3: A DS3 that is channelized into 28 DS1 (1.544 Mbps) signals and include a predefined standard multiplexing scheme as defined in ANSI T1.107a. The M13 DS3 contains parity bits which can be monitored to offer an approximate measure of performance. 43.232 Mbps is customer data (or voice), the remainder being used for framing, synchronization, parity, etc.

C-bit Parity Framed DS3: A DS3 that can be used for subrated or non-subrated DS3 signals. This allows DS3 signal monitoring for end-to-end performance measurement on an in-service basis, transmitted on the maintenance data communications channel. The C-bit parity format is defined in ANSI T1.107a. 43.232 Mbps is customer data (or voice), the remainder being used for framing, synchronization, parity, etc.