Received: 01/31/2011

Status: CANCELLED Effective Date: 02/01/2011

PSC NO: 214 ELECTRICITY LEAF: 7
COMPANY: NIAGARA MOHAWK POWER CORPORATION REVISION: 30
INITIAL EFFECTIVE DATE: FEBRUARY 1, 2011 SUPERSEDING REVISION: 28

STAMPED: Issued in Compliance with Order of the PSC in Case No. 10-E-0050 Issued January 24, 2011

## GENERAL INFORMATION

## III. TERMINOLOGY DEFINITIONS AND ABBREVIATIONS

Equipment – A general reference to customer owned, operated and maintained devices or components specific to the character of service.

Extra Heavy Duty (XHD) – A component having an increased size, thickness or strength necessary to meet the requirements of structural loading conditions.

Facilities – A general reference to company owned, operated and maintained devices, components or infrastructure assemblies specific to the service classification character of service.

Facility Charges – The assignment of a rate to Company owned components which represent the procurement, installation, operation and maintenance value of each in-service asset.

Festoon Outlet (FO) – An electrical receptacle having the proper encasement and weatherproof cover which is integral with or mounted to a street lighting standard or distribution pole to provide a 120V, unmetered electric source for miscellaneous attachment applications requiring service. The assembly is often referred to as a convenience outlet.

Fiberglass (FG, FBGL) – A composite material comprised of epoxy resin and glass fibers or glass cloth, cast into specific product shapes to provide a strong, light weight, non-conductive material.

Floodlight (FL) – A luminaire type that produces a broad dispersion of light to provide illumination of a large area.

Foundation (FD, FDN) – A structure of varied materials and designs that are typically required to support a lighting standard.

Fluorescent (FR) – A linear tube shaped glass envelope containing specific elements that when charged with electricity react with the internal phosphorus coating to emit a white light.

Heavy Duty (HD) – A descriptor used in conjunction with specific facilities to identify units having an increased design load capacity or engineered strength.

 $\label{eq:high-pressure} High \ Pressure \ Sodium \ (HPS \ or \ HS) - A \ high \ intensity \ discharge \ (HID) \ lamp \ technology \ that \ produces \ a \ slightly \ yellow-colored \ light.$ 

Hour (HR) – A unit of time measure equal to 60 minutes.

Illuminating Engineering Society of North America (IESNA or IES) – A lighting industry sponsored illuminating engineering standards organization.

 $In can descent \ (IN, \ INC) - A \ tungsten \ filament \ vacuum \ lamp \ technology \ which \ produces \ a \ moderately \ white light.$