

AT&T Communications of New York, Inc.
P.S.C. No. 25 -- Telephone
Private Line Services
Effective Date: July 21, 2010

Section 9
Leaf No. 21
Revision: 0
Superseding Revision:

SECTION 9 - ACCUNET SPECTRUM OF DIGITAL SERVICES

9.2 SERVICE COMPONENTS AND RATES (Cont'd)

9.2.3 Channel Options (Cont'd)

B. Conditioning (Cont'd)

1. Data Conditioning (Cont'd)

- (b) D-Type conditioning - This conditioning is for the control of signal to C-notched noise ratio and intermodulation distortion. In addition, D-6 conditioning controls phase jitter, attenuation distortion and envelope delay distortion.

The signal to C-notched noise ratio, intermodulation distortion, phase jitter, attenuation distortion and envelope delay distortion parameters for D-Type conditioning are described in Technical Publication - PUB 43202 and PUB 62210 (see Technical Publication Information, Preface).

When a service equipped with D-Type conditioning is used for voice communications, the quality of the voice transmission may not be satisfactory.

When D-Type conditioning is installed subsequent to the start of the service to which it is applied, a charge equal to the installation charge of the service itself will apply in addition to the installation charge for the D-conditioning (USOC NRZDT).

I. D-1 conditioning for two-point services.

	<u>USOC</u>	<u>MONTHLY</u>		<u>INSTALLATION CHARGE</u>	
		<u>Minimum*</u>	<u>Maximum</u>	<u>Minimum*</u>	<u>Maximum</u>
- Per IOC	QHA		-		-

* See 2.5.2 of this tariff.

Issued by: Carol E. Paulsen, Director Regulatory, Dallas, Texas 75202