

AT&T Communications of New York, Inc.
P.S.C. No. 25 -- Telephone
Private Line Services
Effective Date: July 21, 2010

Section 9
Leaf No. 16
Revision: 0
Superseding Revision:

SECTION 9 - ACCUNET SPECTRUM OF DIGITAL SERVICES

9.2 SERVICE COMPONENTS AND RATES (Cont'd)

9.2.3 Channel Options (Cont'd)

- B. Conditioning - Conditioning provides more specific transmission characteristics for ASDS connected to voice grade access or to appropriate office functions. The following types of conditioning apply to end-to-end services using voice grade access. The conditioning parameters stated are based on the assumption that the access will meet the conditioning parameters set forth in the Local Exchange Companies' access service tariffs.
1. Data Conditioning - There are two types of data conditioning: C-Type and D-Type conditioning. C-Type conditioning controls attenuation distortion and envelope delay distortion. D-Type conditioning controls the signal to C-notched noise ratio and intermodulation distortion. D-6 conditioning also controls phase jitter, attenuation distortion and envelope delay distortion. C-Type and D-Type conditioning may be combined on the same channel.
 - a. C-Type conditioning - This conditioning is for the additional control of attenuation distortion and envelope delay distortion. The parameters for C-Type conditioning are described in Technical Publication - PUB 43202 and PUB 62210 (see Technical Publication Information, Preface). Only one kind of C-Type conditioning may be applied to a channel.

Issued by: Carol E. Paulsen, Director Regulatory, Dallas, Texas 75202