

PSC NO: 1 LOCAL EXCHANGE SERVICE
SBC Long Distance, LLC d/b/a SBC Long
Distance, d/b/a AT&T Long Distance
Initial Effective Date: February 9, 2006

Leaf: 134
Revision: 0

Superseding Revision:

B Channel – Provides one voice or data channel on the Primary Rate Interface or Primary Rate Port to the PSTN.

D Channel – Provides one channel for the out-of-band signaling required. A single D Channel may control more than one Primary Rate Interface or Port.

7.2.3 Optional Features

Backup D Channel – In arrangements of two or more Primary Rate Interfaces or Ports, it provides enhanced continuity of Service by allowing a D Channel on one Primary Rate Interface or Port to automatically take over for a failed D Channel on another Primary Rate Interface or Port. A single Backup D Channel may support a maximum of five interfaces or ports.

Calling Number and Name Delivery – Provides the Customer who is receiving a call with the telephone number and the name of the calling party.

Circular Hunt – A switch feature that dynamically points each new call attempt to the next idle B Channel following the last channel either to have accepted a call or the last channel to have attempted to place a call.

Direct Inward Dialing (DID) Numbers – Provides telephone numbers for direct inward dialing. Numbers are available in blocks of ten or one hundred, or as a single number. The assignment and sequence of the numbers may be requested by the Customer in cases where the Company has the number or series of numbers available for use.

Dynamic Channel Allocation – Allows a Customer to designate the quantity of B Channels for call types to be allocated within previously provisioned criteria for either DID or Direct Outward Dialing (DOD) capability.

Issued by: Carol Paulsen, Director-Regulatory Relations, San Antonio, Texas 78215