

..DID: 5890  
..TXT: PSC NO: 8 GAS LEAF: 173  
COMPANY: NATIONAL FUEL GAS DISTRIBUTION CORPORATION REVISION: 1  
INITIAL EFFECTIVE DATE: 10/29/98 SUPERSEDING REVISION: 0  
STAMPS: ISSUED IN COMPLIANCE WITH ORDER IN C. 98-G-1291 DATED 10/21/98.  
Cancelled by 2 Rev. Leaf No. 173 Effective 05/01/2002  
RECEIVED: 10/28/98 STATUS: Cancelled EFFECTIVE: 10/29/98  
SERVICE CLASSIFICATION No. 5

LOAD BALANCING TECHNOLOGY RATE

APPLICABLE TO USE OF SERVICE FOR:

Consumption of natural gas by a non-residential Customer where the gas is used directly in the following types of equipment:

1. Qualified Cogeneration Facilities, as defined in Service Classification No. 17;
2. Gas-Fired Cooling/Dehumidification;
3. Natural Gas Motor Vehicles;
4. Gas-Fired Heat Pumps;
5. Gas-Fired Environmental improvement technologies; or
6. Gas-Fired Equipment which complements electric demand side management.

CHARACTER OF SERVICE:

Firm, continuous, primarily natural gas, minimum B.T.U. content 1,000, normal pressure of not less than four inches water column.

RATE:

The rate has a demand component based on the peak winter month's consumption and a commodity component charging the Customer volumetrically for all gas delivered to the Customer.

Demand Component -

The demand component shall be calculated as follows:

$$(D.M. \times B.D.U.) + (P.G.D.C. \times B.D.U.)$$

D.M. = Demand Margin  
B.D.U. = Billing Demand Units  
P.G.D.C. = Purchased Gas Demand Charge

The Demand Margin is equal to \$.3375/B.D.U. B.D.U. refers to Billing Demand Units, which is the peak billing month

Issued by P.C. Ackerman, President, 10 Lafayette Square, Buffalo NY 14203  
(Name of Officer, Title, Address)