

CenturyLink Communications, LLC
PSC NO. 1 - TELEPHONE
Interexchange Services
Effective Date: July 23, 2015

Section 12
Leaf 2
Revision: 0
Superseding Revision:

12. OBSOLETE PRIVATE LINE SERVICE OFFERINGS

12.1 DATA SERVICES

A. General Description (Cont'd)

2. LightLink Service

LightLink Service provides a high capacity channel for the transmission of 44.736 Mbps isochronous serial data having a line code of Bipolar with Three Zero Substitution (B3ZS). LightLink Service is provided between two points located within the contiguous United States. The required format and interface specifications are contained in Technical Reference Publications 62508 and 62411, and the associated Addendum TR-INS-000342 and TR-NPL-000054. The performance objectives for LightLink Service between the Company's Points of Presence are as follows:

AIRLINE MILES	%NETWORK AVAILABILITY	% ERROR SECONDS
0 - 250 Miles	99.99%	99.90%
251 - 1,000 Miles	99.99%	99.80%
1,001+ Miles	99.98%	99.70%

LightLink service requires T-3 Local Access Facilities as described in Section 11.9 and is subject to the availability of T-3 access by the local exchange company

3. OptiPoint-3 (OC-3) Service

OptiPoint-3 (OC-3) Service is a high speed optical transmission service supporting voice, data, and video applications in a point-to-point fashion. OptiPoint-3 (OC-3) Service offers 155.520 Mbps of bandwidth and provides the equivalent of 2,016 Voice Grade (DS-0) circuits or 84 T-1 facilities. The performance objectives for OptiPoint-3 (OC-3) Service between the Company's Points of Presence are as follows:

Issued by: Chantel Mosby

Director – Tariffs, CenturyLink
100 CenturyTel Drive, Monroe, LA 71203

NY2015-004

Cancelled effective 05/17/2021.