TVC Albany Inc. dba FirstLight Fiber PSC Tariff No. 2 – Telephone Date Effective: November 30, 2016

Section 13 - ISDN - PRIMARY RATE INTERFACE (cont'd)

13.3 PRI Features

- 13.3.1 Virtual NXX Numbers provide the customer to have a virtual presence in rate centers other than the rate center in which the service is provided.
- 13.3.2 "D" Channel Back-Up automatically takes over for a failed "D" channel in case of trouble. This may be subscribed to as part of a 23B+D Channel Back-Up arrangement.
- 13.3.3 Call-by-Call Service Selection provides an option to the dedicated channel configuration by allowing channels to be configured to access multiple services on a per call basis. With this feature, separate facilities are not required for individual services, such as DID, DOD, toll-free services, and local switched access lines.
- 13.3.4 Clear Channel capability allows the customer to transport 64 Kbps over the PRI channels with no constraint on the quantity or sequence of bits using the "Bipolar with Eight Zero Substitution" method of providing bit sequence independence.
- 13.3.5 Non-Facility Associated Signaling (NFAS) allows the D-channel signaling entity to assign calls to channels on more than one interface (including the one containing the D-channel). The collection of these B-channels and the controlling D-channel is called a PRI group. Up to 20 DSI facilities can be assigned to a PRI group.