

MCImetro Access Transmission Services Corp.  
d/b/a Verizon Access Transmission Services

New York Tariff No. 1  
Original Page No. 72

## ACCESS SERVICES

### 5. SWITCHED ACCESS SERVICES (Cont.)

#### 5.5 Switching and Terminating Optional Features (Cont.)

##### 5.5.3 Feature Group D Optional Features (Cont.)

##### 5.5.3.1 Common Switching Optional Features (Cont.)

- d) Service Class Routing: This option provides the capability of directing originating traffic from a Local Switching Center to a Trunk group to a Customer designated Premises, based on the line class of service and service prefix indicator. A domestic Interexchange Carrier may not order more than four different routes per Local Switching Center or Access Tandem. An international Interexchange Carrier may order up to four additional routes.
- e) Feature Group D with 950 Access: This option provides for the routing of originating calls, dialed using a 950-10XX or 950-1XXX Access Code, to the FGD Customer using FGD signaling protocols and technical specifications. The Customer is responsible for distinguishing between standard FGD calls and 950-dialed calls delivered over the same trunks.
- f) Signaling System Seven (SS7): This option provides out of band transmission of SS7 protocol signaling information between the Local Switching Center switching system and the Customer's designated Premises. Prior to installation of any SS7 circuits, the Customer must agree to participate in SS7 certification testing. The Company will provide a testing plan to the Customer, and reserves the right to deny SS7 connectivity if the Customer's circuits do not meet the testing requirements.
- g) Basic Initial Address Message Delivery: This option permits the following optional SS7 signaling call setup parameters: User Service Information, Called Party Number, Calling Party Number, Charge Number, Originating Line Information, Transit Network Selection, Carrier Selection, Service Code and Access Transport.