Status: CANCELLED Received: 12/14/2016 Effective Date: 01/13/2017

TelCove Operations, LLC

NY P.S.C. Tariff No. 1

Initial Effective Date: January 13, 2017

Leaf: 182

Revision: 0

Superseding Revision: 0

Section 7 - BUSINESS NETWORK SWITCHED SERVICES (Cont'd)

7.2 SERVICE DESCRIPTIONS AND RATES (Cont'd)

7.2.3 PBX Trunk Service (Cont'd)

A. General (Cont'd)

Outward-only service provides for one-way calling from the customer-premises equipment to the central office switch. Depending on how the customer programs its system to route calls, a vacant outgoing line can be accessed either directly from the calling line (called DOD, for Direct Outward Dialing, typically invoked by dialing "9"), or from the attendant position (called non-DOD). Incoming calls cannot be received over a trunk with outward-only service.

Combination service provides for two-way calling between the central office switch and customer-premises equipment. Depending on how the customer programs its system to route calls, inward calls can be either DID or non-DID, and outward calls can be either DOD or non-DOD. Since most combination trunks provide for DID and DOD calling, and they are often referred to as DIOD (Direct Inward/Outward Dialing) trunks.

For DID configured PBX trunks additional charges apply for Direct Inward Dial Station numbers.

Each DS0 level Trunk has the following characteristics:

Terminal Interface: 2-wire or 4-wire, as required for the

provision of service

Signaling Type: Loop, Ground, E&M I, II, III

Pulse Type: Dual Tone Multi-Frequency (DTMF) or Dial

Pulse (DP)

Calling Direction: One-way inward-only, one-way outward-only,

or two-way inward and outward

By: General Counsel – Regulatory Policy

1025 Eldorado Boulevard Broomfield, CO 80021