

Media Three Corporation, Inc.
P.S.C. No. 3 – Access
Effective Date: 11/10/2013

Leaf: 111
Revision 0
Superseding Revision:

ACCESS SERVICE

4. SWITCHED ACCESS SERVICE (Cont'd)

4.4 Transmission Specifications (Cont'd)

4.4.1 Standard Transmission Specifications (Cont'd)

(A) Type A Transmission Specifications

Type A Transmission Specifications are provided with the following parameters:

(1) Loss Deviation

The maximum Loss Deviation of the 1004 Hz loss relative to the Expected Measured Loss (EML) is ± 2.0 dB

(2) Attenuation Distortion

The maximum Attenuation Distortion in the 404 to 2804 Hz frequency band relative to the loss at 1004 Hz is -1.0 dB to +3.0 dB.

(3) C-Message Noise

The maximum C-Message Noise for the transmission path at the route miles listed is less than or equal to:

| <u>Route Miles</u> | <u>C-Message Noise</u> |
|--------------------|------------------------|
| less than 50 | 32 dBrnCO |
| 51 to 100 | 34 dBrnCO |
| 101 to 200 | 37 dBrnCO |
| 201 to 400 | 40 dBrnCO |
| 401 to 1000 | 42 dBrnCO |

(4) C-Notch Noise

The maximum C-Notch Noise, utilizing a -16 dBm0 holding tone, is less than or equal to 45 dBrnCO.

Issued By: Paul Butler, Vice President, 254 36th Street, Unit 12 – Suite C304, Brooklyn, NY 11232

Cancelled by supplement No. 1 effective 06/13/2022