Media Three Corporation, Inc. P.S.C. No. 3 – Access Effective Date: 11/10/2013 Leaf: 110 Revision 0 Superseding Revision:

ACCESS SERVICE

4. SWITCHED ACCESS SERVICE (Cont'd)

4.4 Transmission Specifications

Each Switched Access Service transmission path is provided with a standard transmission performance. There are three different standard performances (Types A, B and C). The standard for a particular transmission path is dependent on the Feature Group, the Entrance Facility, the Interface Group and whether the service is direct end office routed or routed via an access tandem. The available transmission specifications are set forth in 4.4.1 following. Data Transmission Parameters are also provided with each Switched Access Service transmission path. The Telephone Company will, upon notification by the customer that the data parameters set forth in 4.4.2(A) or 4.4.2(B) are not being met, conduct tests independently or in cooperation with the customer, and take any necessary action to insure that the data parameters are met.

The Telephone Company will maintain existing transmission specifications on service configurations installed prior to January 1, 1984, except that service configurations having performance specifications exceeding the standards listed in this provision will be maintained at performance levels specified in this tariff.

The transmission specifications contained in this Section are immediate action limits. Acceptance limits are set forth in Technical Reference TR-NPL-000334, Issue No. 1. This Technical Reference also provides the basis for determining Switched Access Service maintenance limits.

Transmission specifications for CCSA signaling connections are set forth in the Technical Publication TR-TSV-000905.

4.4.1 Standard Transmission Specifications

Following are descriptions of the three Standard Transmission Specifications available with Switched Access Service Feature Groups. The specific applications in terms of the Feature Groups, Entrance Facilities and Interface Groups with which Feature Group Standard Transmission Specifications are provided are set forth in 4.2.1(C), 4.2.2(C), 4.2.3(C), and 4.2.4(D) preceding.