

Media Three Corporation, Inc.
P.S.C. No. 3 – Access
Effective Date: 11/10/2013

Leaf: 113
Revision 0
Superseding Revision:

ACCESS SERVICE

4. SWITCHED ACCESS SERVICE (Cont'd)

4.4 Transmission Specifications (Cont'd)

4.4.1 Standard Transmission Specifications (Cont'd)

(B) Type B Transmission Specifications

Type B Transmission Specifications is provided with the following parameters:

(1) Loss Deviation

The maximum Loss Deviation of the 1004 Hz loss relative to the Expected Measured Loss (EML) is 2.5 dB.

(2) Attenuation Distortion

The maximum Attenuation Distortion in the 404 to 2804 Hz frequency band relative to loss at 1004 Hz is -2.0 dB to +4.0 dB.

(3) C-Message Noise

The maximum C-Message Noise for the transmission path at the route miles listed is less than or equal to:

C-Message Noise*

<u>Route Miles</u>	<u>Type B1</u>	<u>Type B2</u>
less than 50	32 dBrnCO	35 dBrnCO
51 to 100	33 dBrnCO	37 dBrnCO
101 to 200	35 dBrnCO	40 dBrnCO
201 to 400	37 dBrnCO	43 dBrnCO
401 to 1000	39 dBrnCO	45 dBrnCO

Issued By: Paul Butler, Vice President, 254 36th Street, Unit 12 – Suite C304, Brooklyn, NY 11232

Cancelled by supplement No. 1 effective 06/13/2022