

Media Three Corporation, Inc.
P.S.C. No. 3 – Access
Effective Date: 11/10/2013

Leaf: 123
Revision 0
Superseding Revision:

ACCESS SERVICE

4. SWITCHED ACCESS SERVICE (Cont'd)

4.5 Obligations of the Telephone Company (Cont'd)

4.5.4 Trunk Group Measurement Reports

Subject to available, the Telephone Company will make available trunk group data in the form of usage in CCS, peg count and overflow, to the customer based on previously agreed to intervals.

4.5.5 Determination of Number of End Office Transport Terminations (End Office Trunk Ports)

For analog entry switches, a termination will be provided for each transmission path provided. For digital entry switches, an equivalent termination will be provided for each transmission path provided.

4.5.6 Design Blocking Probability

The Telephone Company will monitor the facilities used in the provision of Switched Access Service to meet the blocking probability criteria as set forth in the following.

The design blocking objective will be no greater than one percent (.01) between the point of termination at the customer's premises or a collocated interconnection location and the end office switch, whether the traffic is directly routed without an alternate route or routed via an access tandem. Standard traffic engineering methods as set forth in reference document Technical Reference PUB SR EOP-000191 Trunk Traffic Engineering Concepts and applications will be used by the Telephone Company to determine the number of transmission paths required to achieve this level of blocking.

Issued By: Paul Butler, Vice President, 254 36th Street, Unit 12 – Suite C304, Brooklyn, NY 11232

Cancelled by supplement No. 1 effective 06/13/2022