
ACCESS SERVICE

EXPLANATION OF SYMBOLS AND ABBREVIATIONS

SYMBOLS

- (C)** To signify changed listing, rule, or condition which may affect rates or charges.
- (D)** To signify discontinued material, including listing, rate, rule, or condition.
- (I)** To signify an increase.
- (M)** To signify material relocated from or to another part of tariff schedule with no change in text, rate, rule or condition.
- (N)** To signify new material including listing, rate, rule or condition.
- (R)** To signify reduction.
- (S)** To signify reissued material.
- (T)** To signify change in wording of text but not change in rate, rule, or condition.
- (Z)** To signify a typographical correction.

ABBREVIATIONS

- B8ZS** - Bipolar with 8-Zero Substitution; a line coding technique which permits DS0 and DS1 transmission with 15 consecutive zeros. B8ZS support 64 KBPS clear channel transmission.
- DCS** - Digital Cross Connect System.
- DS0** - Digital Signal Level 0; a dedicated, full duplex digital channel with line speeds of 2.4, 4.8, 9.6, 19.2, 56 or 64 Kbps.
- DS1** - Digital Signal Level 1; a dedicated, high capacity, full duplex channel with a line speed of 1.544 Mbps isochronous serial data having a line signal format of either Alternate Mark Inversion (AMI) or Bipolar with 8 Zero Substitution (B8ZS) and either Superframe (D4) or Extended Superframe (ESF) formats. DS1 Service has the equivalent capacity of 24 Voice Grade or DS0 services.
- DS3** - Digital Signal Level 3; a dedicated, high capacity, full duplex channel with a line speed of 44.736 Mbps isochronous serial data having a line code of bipolar with three zero substitution (B3ZS). Equivalent capacity of 28 DS1 Services.