

ADVANCED DATA SERVICES

## DESCRIPTION OF ADVANCED DATA SERVICES (Continued)

- 4.3 ASYNCHRONOUS TRANSFER MODE CELL RELAY SERVICE (ATM CRS) (Cont'd) (N)  
**(Effective February 15, 2013, Asynchronous Transfer Mode Cell Relay Service (ATM CRS) is no longer available to new customers. See Paragraph 4.3.0 preceding.)** (N)

- 4.3.4 Service Components (Cont'd)  
(B) Port Only Connections (Cont'd) J

Customers may access Port Only Connections via Company-provided digital access facilities or via facilities provided by another carrier. When access facilities are provided by the Company, the associated regulations, rates and charges under the appropriate Company Tariff shall apply in addition to the regulations, rates and charges associated with ATM CRS. Company-provided access facilities may also be provisioned on an Individual Case Basis (ICB) where access facilities are not generally available under the applicable tariff. Interconnection charges to connect access line services provided by the Company or another carrier may apply and will be billed separately. Any special construction or nonstandard charges assessed by the carrier supplying the access facilities will be the responsibility of the Customer.

- (C) Permanent Virtual Circuit (PVC) (M)

The PVC defines a virtual connection across a UNI between the Customer premises and Company's ATM CRS hub. Each UNI requires at least one PVC in order for Customer traffic to traverse the network. Each ATM cell carries a unique tag which identifies that ATM CRS cell as belonging to a particular PVC. A PVC is a logical channel connecting two or more Customer-designated premises with virtual connections through a Company provided ATM CRS switch(es). The PVCs may be provided on a point-to-point or point-to-multipoint basis. When a PVC is provided as a point-to-point virtual connection, transmission is bi-directional allowing for ATM CRS cells to be transmitted or received over the same PVC. For point-to-multipoint virtual connections, transmission is provided as transmit only. The virtual connection is set up by the Company based on information contained on a service order rather than by dial-up signaling. J

PVCs consist of two types: Virtual Channel Connections (VCCs) and Virtual Path Connections (VPCs). A VCC is a type of PVC with independent identity and defined service parameters that are provisioned via service order, and cannot be altered by the Customer without additional service order activity. A VPC is a type of PVC with defined service parameters that is provisioned via service order. Customers may provision their own virtual channels within the VPC, provided that the sum of the service parameters of all of the virtual channels does not exceed the aggregate service parameters of the VPC.