

ADVANCED DATA SERVICES

DESCRIPTION OF ADVANCED DATA SERVICES (Continued)

- 4.3 ASYNCHRONOUS TRANSFER MODE CELL RELAY SERVICE (ATM CRS) (Cont'd)
(Effective February 15, 2013, Asynchronous Transfer Mode Cell Relay Service (ATM CRS) is no longer available to new customers. See Paragraph 4.3.0 preceding.) (N)
(N)

4.3.6 Regulations (Cont'd)

D. CLASS OF SERVICE PARAMETERS (Cont'd)

2. **Variable Bit Rate (VBR) (Real Time/Non-Real Time)** supports the following parameters:
 - a. Sustained Cell Rate (SCR) consists of customer specified in increments of 64 Kbps up to the maximum speed of the UNI.
 - b. Peak Cell Rate (PCR) consists of customer selectable increments of 64 Kbps up to line rate. Default is 200% of SCR for PVCs. (The ratio of PCR to SCR will be signaled by CPE for SVCs. Therefore there is no default value.)
 - c. Non-conforming cells are discarded.
 - d. Cell Delay Variation Tolerance (CDVT) levels are as follows:

DS1 = 600 microseconds
DS3 = 600 microseconds
OC3c = 600 microseconds
OC12c = 600 microseconds
 - e. Maximum Burst Size (MBS):

Is customer selectable
Has a default of 100 cells on PVCs
Is dependent upon the signaling on SVCs
3. **Unspecified Bit Rate (UBR)** supports the following parameters:
 - a. Has no QoS descriptors, i.e. CBR or VBR
 - b. Is a Best-effort service
 - c. Discards cells exceeding network capacity